

Onion topper



Topper

- Mechanic driven (PTO)
 - PTO with freewheel
 - Rear mount
 - Central tensioner
 - Heavy-duty gearbox
- Double bearing on axles
 - Double hydraulic height adjustment
 - Available in different widths
 - All around protective plating



Automatic depth control



Side delivery



Knives in a topper with side delivery



Wide model topper



Wheeltrack cutting disc



Knives in standard topper



Remote control for (automatic) depth control



Options

- Automatic depth control
- Remote control for (automatic) depth control
- Front mount
- Wide model (cuts wheeltrack and first row in the next bed, only for front mount machines without side delivery)
- Combi mount (front and rear)
- LoadSensing connection for depth control
- Wheeltrack cutting disc
- Lights
- Side delivery (closed version)

Wheeltrack	1.50	1.80	2.00	2.25
Working width	1.40	1.65	2.00	2.00
Working width wide model	1.70	x	x	2.45
PTO (front/rear)	750/540			
Dimensions L*W*H (m)	2,0*1,90*1,3	2,15*2,15*1,3	2,3*2,6*1,3	2,3*2,6*1,3
Knives	3x2	3x2	4x2	4x2
Wheels	3	3	4	4
Wheels with side delivery or wide model	3	3	3	3
Height adjustment (cm)	40			
Weight (kg) *	660-715	695-795	925-960	925-1060

* Depending on options

Product range



Onion windrowers



Haulm toppers



Onion loaders



Box trailers



3-bed windrowers



3-bed toppers



Potato windrowers



Conveyor belts

Dealer

ELLENS
SAMON
LANDBOUWTECHNIEK BV

Ellens Landbouwtechniek BV
Ploegstraat 4
8308 AA Nagele
The Netherlands

T +31 527 652 500
F +31 527 652 916
E info@samon.nl
W www.samon.nl

